

HWT-E3040-I

4MP IR Motorized Lens Dome Network Camera



Features

- ▶ H.265 /H.264/MJPEG coding
- ▶ Max.resolution: 4MP (2560 × 1440)
- ▶ ICR auto switch, true day / night vision
- ▶ 3D DNR, WDR, HLC, BLC, smart IR, etc.
- ▶ 30m IR night view distance
- ▶ Built-in micro SD card slot, up to 256GB 1CH built-in MIC;
- ▶ 1CH audio input
- ▶ DC12V/PoE power supply
- ▶ IP 67 ingress protection
- ▶ Support three streams

Technical Specifications

Model		HWT-E3040-I
Major Specifications		
Camera	Image Sensor	1 / 3 "CMOS
	Maximum Resolution	2560×1440
	Effective Pixels	4MP
	Supported Resolution	4MP (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, 480× 240, CIF
	Video Compression Standard	Main stream: H.265 / H.264 Sub/Third stream: H.265 / H.264 / MJPEG
	Frame Rate	Main Stream: 60Hz: 4MP/3MP/1080P/720P(1~30fps); 50Hz: 4MP/3MP/1080P/720P(1~25fps) Sub Stream: 60Hz: 720P/D1/CIF (1~30fps);50Hz: 720P/D1/CIF (1~25fps) Third Steam: 60Hz: D1/480× 240/CIF (1~30fps);50Hz: D1/480× 240/CIF(1~25fps)
	Code Stream	Triple streams
	Video Steam	VBR / CBR
	Focal Length	2.8~12mm
	Max Aperture	F1.6
	Lens Aperture Type	Fixed Iris
	Angle Of View	Horizontal : 92 °~31 °; Vertical: 48 °~17.2°; Diagonal: 112 °~ 35.6 °
	IR Range	30m
	Infrared Light	Support
	Minimum Illumination	0.005 lux @F1.6, AGC ON; 0 lux with IR
Function	Motion Detection	Support
	Email Alert	Support
	Image Rotation	Support (Mirror/Flip)
	Wide Dynamic	120dB
	SD Card	Support
	External Audio Input	1CH Audio Input
Network	Ethernet	10M/100M Ethernet, RJ45 port
	Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, QoS
	ONVIF	ONVIF 2.4(Profile S)
	WEB Interface	English
General Specifications		
Power Type	DC12V/PoE	
Power Consumption	< 8W	
Operating Temperature	- 30 °C ~ 60 °C (-22°F~140°F)	
Operating Humidity	Less than 95 % (non-condensing)	
IP Rating	IP 67	
Weight	Approx. 0.65KG	
Dimensions (mm)	Ø 111.5 × 99.6	
Material	Metal	

Dimensions

