

E1T-2LRV(2.8)

**2MP Dual Light Bullet Camera
with Mic**



Features

- 1/3" CMOS Sensor
- Support H.264/H.265
- Support ONVIF Profiles
- Ingress Protection: IP67
- 2 White Lights and 2 IR Lights
- Support DWDR, 3D Noise Reduction, Backlight Compensation, and White Balance, Suitable for Different Monitoring Environments
- Support Audio Input, Audio and Video Synchronization
- Support Mobile App Remote Monitoring
- Build-in MIC

Model E1T-2LRV(2.8)		
Major Specifications		
Camera	Image Sensor	1/ 3" CMOS
	Maximum Resolution	1920 (H)*1080 (V)
	Effective Pixels	2.0MP
	Video Compression Standard	H.265/H.264
	Frame Rate	Default 2MP@30fps(Main Stream) Subcode stream:448P(800*448)/D1(704*576)/360P(640*360)/ CIF(352*288)
	Code Stream	Dual Stream
	Video Steam	Support VBR,CBR
	Focal Length	2.8mm
	Max Aperture	F2.0
	Lens Aperture Type	Fixed iris
	Angle of View	H 100.5° , V 55.9° , D: 116.9°
	White Light Range	20m
	White Light	2
	IR Range	30m
	Infrared light	2
	Minimum illumination	0.02lux
Function	Motion Detection	Support
	Email Alert	Not Support
	Image Rotation	Support
	Wide Dynamic	DWDR
	SD card	Not Support
	External Audio Input	Not Support
	Ethernet	10M/100M Ethernet, RJ45 port
Network	Protocol	ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS
	Client	HOLOZ VMS, HOLOZ App
	WEB Interface	Support English/Chinese/Russian/Japanese/Korean/Italiano/Português
Intelligent	Intrusion Detection	Support
	Crossing Detection	Support
	Off-duty Detection	Support
	Passenger Flow Statistics	Support
General Specifications		
Power type	12 V DC 1 A and PoE (IEEE 802.3af)	
Power consumption	Day ≤3W Night ≤7W	
Operating temperature	-30°C to +60°C	
Operating humidity	10% to 90% (Non-Condensing)	
IP rating	IP67	
Weight	350g	
Dimension	179mm*67.2mm*62.5mm (L*W*H)	
Dimension (With Package)	180mm*70mm*65mm (L*W*H)	

Dimensions

