

E3T-5LRV(2.8)

**5MP Dual Light Dome Camera
with MIC**



Features

- 1/3" CMOS Sensor
- Support H.264/H.265
- Support ONVIF Profiles
- Ingress Protection: IP66
- 3 White Lights and 3 IR Lights
- Support DWDR, 3D Noise Reduction, Backlight Compensation, and White Balance, Suitable for Different Monitoring Environments
- Support Audio Input, Audio and Video Synchronization
- Support Mobile App Remote Monitoring
- Build-in MIC

Model E3T-5LRV(2.8)
Major Specifications

Camera	Image Sensor	1/ 3" CMOS
	Maximum Resolution	2880 (H)*1624 (V)
	Effective Pixels	5.0MP
	Video Compression Standard	H.265/H.264
	Frame Rate	Main stream:5MP(2880*1624)@20fps/ 4MP(2560*1440)@25fps Subcode stream:448P(800*448)/D1(704*576)/360P(640*360)/ CIF(352*288
	Code Stream	Dual Stream
	Video Steam	Support VBR,CBR
	Focal Length	2.8mm
	Max Aperture	F2.0
	Lens Aperture Type	Fixed iris
	Angle of View	H 98° , V 53° , D: 113°
	White Light Range	20m
	White Light	3
	IR Range	30m
	Infrared light	3
	Minimum illumination	0.02lux

Function	Motion Detection	Support
	Email Alert	Not Support
	Image Rotation	Support
	Wide Dynamic	Support DWDR
	SD card	Not Support
Network	External Audio Input	Not Support
	Ethernet	10M/100M Ethernet, RJ45 port
	Protocol	ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS
	Client	HOLAZ VMS, HOLAZ App
	WEB Interface	Support English/Chinese/Russian/Japanese/Korean/Italiano/Português
Intelligent	Intrusion Detection	Support
	Crossing Detection	Support
	Off-duty Detection	Support
	Passenger Flow Statistics	Support

General Specifications

Power type	12 V DC 1 A and PoE (IEEE 802.3af)
Power consumption	Day ≤3W Night ≤7W
Operating temperature	-30°C to +60°C
Operating humidity	10% to 90% (Non-Condensing)
IP rating	IP66
Weight	290g
Dimension	101.7mm*101.7mm*102.4mm (L*W*H)
Dimension (With Package)	115mm*115mm*110mm (L*W*H)

Dimensions

